

# Protectcoat Algae CP

According to EC-Regulation 2015/830

## Section 1. Identification of the substance and of the company/undertaking

### Company details:

Protectcoat International  
Spinding 16  
5431 SN CUIJK  
The Netherlands  
+31 (0)85-0655797  
www.protectcoatint.com

**Trade name** : Protectcoat Algae CP

### 1.2 Relevant identified uses of the substance or mixture and uses advised

Cleaning liquid

### 1.3 Emergency telephone number:


EU: call 112

## Section 2. Hazards Identification

### 2.1 Classification of the substance or mixture

Skin Corr. 1B; H314  
Eye Dam. 1; H318  
Acute Tox. 4; H332 Aquatic Acute 1; H400  
Aquatic Chronic 3; H412  
See full text of H-phrases in section 2.2.

### 2.2 Label elements



### Signal word:

Danger

### Hazard statements

Causes severe skin burns and eye damage H314  
Harmful if inhaled. (H332)  
Very toxic to aquatic life. (H400)  
Toxic to aquatic life with long lasting effects. (H411)

# Protectcoat Algae CP

According to EC-Regulation 2015/830

## Section 2. Hazards Identification

### Precautionary Statements

**General:** If medical advice is needed, have product container or label at hand. (P101).

Keep out of reach of children. (P102).

**Prevention:** Do not breathe mist/vapours/fume/spray. (P260).

**Response:** IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. (P303+P361+P353).

**Storage:** Store locked up. (P405).

**Disposal:** Dispose of contents/container to an approved waste disposal plant. (P501).EU: call 112

### Identity of the substances primarily responsible for the major health hazards

Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides; sodium hydroxide;

Quaternary, ammonium, compounds, C12-14-alkyl, hydroxyethyl, dimethyl, ethoxylated, chlorides

### Additional labelling

Not applicable

### Unique formula identifier (UFI)

M72K-YKV3-R100-KK47

### 2.3. Other hazards

Not applicable

### Additional warnings

Tactile warning. If this product is sold in retail, it must be delivered with child-resistant fastening.

### VOC (volatile organic compound)

Not applicable

## Section 3. Composition information on ingredients

NAME: Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides  
 IDENTIFICATION NOS.: CAS-no: 68424-85-1 EC-no: 270-325-2 REACH-no: 01-2119965180-41  
 CONTENT: 15 - <25%  
 CLP CLASSIFICATION: Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 1  
 H302, H314, H318, H400, H410 (M-acute = 10) (M-chronic = 1)

NAME: sodium hydroxide  
 IDENTIFICATION NOS.: CAS-no: 1310-73-2 EC-no: 215-185-5 REACH-no: 01-2119457892-27  
 Index-no: 011-002-00-6  
 CONTENT: 1-<2.5%  
 CLP CLASSIFICATION: Met. Corr. 1, Skin Corr. 1A, Eye Dam. 1  
 H290, H314, H318

NAME: Quaternary ammonium compounds, C12-14 alkyl, hydroxyethyl, dimethyl, ethoxylated, chlorides  
 IDENTIFICATION NOS.: CAS-no: 1554325-20-0 EC-no: 810-152-7  
 CONTENT: 0,25 - <1%  
 CLP CLASSIFICATION: Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Aquatic Acute 1 H302, H315, H318, H400  
 (M-acute = 1)

# Protectcoat Algae CP

According to EC-Regulation 2015/830

## Other information

ATEmix(inhale, vapour) > 20

ATEmix(inhale, dust/mist) > 5

ATEmix(inhale, gas) = 14693.88 - <= 20000

ATEmix(dermal) > 2000

ATEmix(oral) > 2000

Eye Cat. 1 Sum =  $\sum(C_i/S(G)CL_i) = 6.8 - 10.2$

Skin Cat. 2 Sum =  $\sum(C_i/S(G)CL_i) = 21.2 - 31.8$

N chronic (CAT 2) Sum =  $\sum(C_i/(M(\text{chronic})_i * 25) * 0.1 * 10^{CAT_i}) = 7.84 - 11.76$

N acute (CAT 1) Sum =  $\sum(C_i/M(\text{acute})_i * 25) = 7.8592 - 11.7888$

Detergent: 15 - 30%: BENZALKONIUM CHLORIDE < 5%: CATIONIC SURFACTANTS

## Section 4. First aid measures

### 4.1 Description of first aid measures

#### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet.

The doctor can contact The National Poisons Information Service: Dial 0344 892 0111 (24 h service).

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### Inhalation

Bring the person into fresh air and stay with him/her. Make sure the injured person is continuously monitored. Prevent shock by keeping the injured person warm and calm. If breathing ceases, give mouth-to-mouth resuscitation. If unconscious, roll the injured person into recovery position. Call an ambulance.

#### Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with soap and water.

#### Eye contact

Remove contact lenses. Flush eyes with plenty of water or salt water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing.

#### Ingestion

In the case of ingestion, contact a doctor immediately and bring the safety data sheet or label. If the person is conscious, give them water. DO NOT try to induce vomiting, unless this is recommended by a doctor. Hold head facing down to prevent vomit returning to the mouth and throat. Prevent shock by keeping the injured person warm and calm. Initiate immediate resuscitation if breathing stops. If unconscious, roll the injured person into recovery position. Call an ambulance.

#### Burns

Not applicable

# Protectcoat Algae CP

According to EC-Regulation 2015/830

## 4.2. Most important symptoms and effects, both acute and delayed

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, -irritations and burns in the respiratory organs -as well as coughing. Dermal contact and contact with the eye cause irreversible effects. This product contains substances that may trigger an allergic reaction to predisposed persons. This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned: Get immediate medical advice/attention.

### Information to medics

Bring this safety data sheet.

## Section 5. Firefighting measures

### 5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist.

### 5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Halogenated compounds. Nitrogen oxides. Carbon oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

## Section 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid inhalation of vapours from spilled material. Avoid direct contact with spilled substances.

### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities. It is recommended to install waste collection trays to prevent emissions to the waste water system and surrounding environment.

### 6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

### 6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures

# Protectcoat Algae CP

According to EC-Regulation 2015/830

## Section 7. Handling and storage

### 7.1. Precautions for safe handling

Smoking, storage of tobacco, consumption and storage of food or liquids are not allowed in the workrooms. It is recommended to install waste collection trays to prevent emissions to the waste water system and surrounding environment. See section on 'Exposure controls/personal protection' for information on personal protection. Avoid direct contact with the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

### Storage temperature

Room temperature 18 to 23°C

### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

## Section 8. Exposure controls – personal protection

### 8.1. Control parameters

#### OEL

Sodium hydroxide Long-term exposure limit (8-hour TWA reference period): - ppm | - mg/m<sup>3</sup> Short-term exposure limit (15-minute reference period): - ppm | 2 mg/m<sup>3</sup>

#### DNEL / PNEC

DNEL (sodium hydroxide): 1 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - General population

DNEL (sodium hydroxide): 1 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - Workers

DNEL (sodium hydroxide): 2 mg/kg bw/d

Exposure: Dermal

Duration of Exposure: Short term – Local effects - Workers

DNEL (sodium hydroxide): 2 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Short term – Local effects – Workers

DNEL (Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides): 3.96 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides): 5.7 mg/kg bw/day

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

# Protectcoat Algae CP

According to EC-Regulation 2015/830

DNEL (Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides): 1.64 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL (Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides): 3.4 mg/kg/day

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

DNEL (Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides): 3.4 mg/kg bw/day

Exposure: Oral

Duration of Exposure: Long term – Systemic effects - General population

PNEC (Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides): 0.0009 mg/l

Exposure: Freshwater

PNEC (Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides): 0.00096 mg/l

Exposure: Marine water

PNEC (Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides): 0.4 mg/l

Exposure: Sewage Treatment Plant

PNEC (Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides): 12.27 mg/kg dw

Exposure: Freshwater sediment

PNEC (Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides): 13.09 mg/kg dw

Exposure: Marine water sediment

PNEC (Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides): 7 mg/kg dw

Exposure: Soil.

## 8.2. Exposure controls

Compliance with the accepted occupational exposure limits values should be controlled on a regular basis.

### General recommendations

Observe general occupational hygiene standards.

### Exposure scenarios

There is no appendix to this safety data sheet.

### Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

### Appropriate technical measures

Ensure emergency eyewash and -showers are clearly marked.

### Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

### Measures to avoid environmental exposure

Keep containment materials near the workplace. If possible, collect spillage during work.

# Protectcoat Algae CP

According to EC-Regulation 2015/830

**Individual protection measures, such as personal protective equipment**



## Generally

Use only CE marked protective equipment.

## Respiratory Equipment

In case of spray application: Use mask with particle filter S/SL

## Skin protection

Dedicated work clothing should be worn. Wear a protective suit in the event of prolonged periods of work with the product.

## Hand protection

Nitrile rubber Breakthrough time: > 480 minutes (Class 6)

## Eye protection

Wear safety glasses with side shields.

## Section 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Form	Liquid
Colour	Yellow
Odour	Characteristic
Odour threshold (ppm)	No data available.
pH	13
Viscosity (40°C)	No data available.
Density (g/cm <sup>3</sup> )	1
<b>Phase changes</b>	
Melting point (°C)	No data available.
Boiling point (°C)	100
Vapour pressure	No data available.
Decomposition temperature (°C)	No data available.
Evaporation rate (n-butylacetate = 100)	No data available.
<b>Data on fire and explosion hazards</b>	
Flash point (°C)	No data available.
Ignition (°C)	No data available.
Auto flammability (°C)	No data available.
Explosion limits (% v/v)	No data available.
Explosive properties	No data available.
<b>Solubility</b>	
Solubility in water	Soluble
n-octanol/water coefficient	No data available.

# Protectcoat Algae CP

According to EC-Regulation 2015/830

## 9.2. Other information

Solubility in fat (g/L)

No data available.

## Section 10. Stability and reactivity

### 10.1. Reactivity

No data available

### 10.2. Chemical stability

The product is stable under the conditions, noted in the section "Handling and storage".

### 10.3. Possibility of hazardous reactions

Nothing special

### 10.4. Conditions to avoid

Nothing special

### 10.5. Incompatible materials

Strong acids, strong bases and strong reducing agents.

### 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

## Section 11. Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Substance: Quaternary, ammonium, compounds, C12-14-alkyl, hydroxyethyl, dimethyl, ethoxylated, chlorides

Species: Rat

Test: LD50

Route of exposure: Oral

Result: >300-2000 mg/kg

Substance: sodium hydroxide

Species: Rat

Test: LD50

Route of exposure: Oral

Result: 325 mg/kg bw

Substance: Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides

Species: Rat

Test: LD50

Route of exposure: Oral

Result: 300-2000 mg/kg

Substance: Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides

Species: Rabbit

Test: LD50

Route of exposure: Dermal

Result: 3340mg/kg



# Protectcoat Algae CP

According to EC-Regulation 2015/830

## **Skin corrosion/irritation**

Causes severe skin burns and eye damage.

Data on substance: Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides Test: no guideline followed Organism: Rabbit Result: corrosive

## **Serious eye damage/irritation**

Causes serious eye damage.

## **Respiratory or skin sensitization**

No data available.

## **Section 12. Ecological information**

### **12.1 Toxicity**

Substance: Quaternary, ammonium, compounds, C12-14-alkyl, hydroxyethyl, dimethyl, ethoxylated, chlorides

Species: Fish

Test: LC50

Duration: 96 h

Result: 10-100 mg/l

Substance: Quaternary, ammonium, compounds, C12-14-alkyl, hydroxyethyl, dimethyl, ethoxylated, chlorides

Species: Daphnia

Test: EC50

Duration: 48 h

Result: 1-10mg/l

Substance: Quaternary, ammonium, compounds, C12-14-alkyl, hydroxyethyl, dimethyl, ethoxylated, chlorides

Species: Algae

Test: EC50

Duration: 72 h

Result: 1-10 mg/l

Substance: sodium hydroxide

Species: Fish

Test: LC50

Duration: 96h

Result: 33-189 mg/l

Substance: sodium hydroxide

Species: Daphnia

Test: EC50

Duration: 48h

Result: 40-240 mg/l

Substance: Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides

Species: Daphnia

Test: EC50

Duration: 48h

Result: 0.01-0.1 mg/l

# Protectcoat Algae CP

According to EC-Regulation 2015/830

Substance: Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides

Species: Algae

Test: EC50

Duration: 72h

Result: 0.01-0.1 mg/l

Substance: Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides

Species: Fish

Test: LC50 Duration: 96h

Result: 0.1-1 mg/l

Substance: Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides

Species: Algae

Test: NOEC

Duration: 72h

Result: 0.001-0.01 mg/l

## 12.2. Persistence and degradability

Substance	Biodegradability	result
Quaternary, ammonium, compounds	Yes	>60%
Quaternary ammonium compounds, ...	Yes	>60%
sodium hydroxide	Yes	no data available

## 12.3. Bioaccumulative potential

Substance	Potential bioaccumulation
Quaternary, ammonium, compounds	No
Quaternary, ammonium, compounds	No
sodium hydroxide	No
	LowPow: - 1.93

## 12.4. Mobility in soil

Quaternary ammonium compounds, ...: Log Koc= -1.449967, Calculated from LogPow ().

## 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

## 12.6. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms. This product contains substances, which may cause adverse long-term effects to the aquatic environment.

# Protectcoat Algae CP

According to EC-Regulation 2015/830

## Section 13. Disposal considerations

### 13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

#### Waste

EWC code –

#### Specific labelling

Not applicable

#### Contaminated packing

Contaminated packaging must be disposed of similarly to the product.

## Section 14. Transport Information

14.1 – 14.4

This product is within scope of the regulations of transport of dangerous goods.

#### ADR/RID

14.1. UN number 1760

14.2. UN proper shipping name CORROSIVE LIQUID, N.O.S.

14.3. Transport hazard class(es) 8

14.4. Packing group III Notes - Tunnel restriction code E

#### IMDG

UN-no. 1760 Proper Shipping Name CORROSIVE LIQUID, N.O.S.

Class 8 PG\* III

EmS: F-A S-B

MP\*\* No

Hazardous constituent –

#### IATA/ICAO

UN-no. 1760

Proper Shipping Name CORROSIVE LIQUID, , N.O.S.

Class 8

PG\* III

14.5. Environmental hazards

–

14.6. Special precautions for user

–

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

(\*) Packing group | (\*\*) Marine pollutant

# Protectcoat Algae CP

According to EC-Regulation 2015/830

## Section 15. Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Restrictions for application

People under the age of 18 shall not be exposed to this product cf. Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

#### Demands for specific education

-

#### Additional information

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

#### Seveso

Seveso III Part 1: E1

#### Biocidal reg. no.

Not applicable

#### Sources

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work. Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP). Regulation (EC) 1907/2006 (REACH).

### 15.2. Chemical safety assessment

No

# Protectcoat Algae CP

According to EC-Regulation 2015/830

## Section 16. Other information

### Full text of H-phrases as mentioned in section 3

- H290 - May be corrosive to metals.
- H302 - Harmful if swallowed.
- H314 - Causes severe skin burns and eye damage.
- H315 - Causes skin irritation.
- H318 - Causes serious eye damage.
- H400 - Very toxic to aquatic life.
- H410 - Very toxic to aquatic life with long lasting effects.

### The full text of identified uses as mentioned in section 1

-

### Additional label elements

Not applicable

### Other

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the mixture is based on: The classification of the mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) The classification of the mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) The classification of the mixture in regard of skin corrosion and serious eye damage is based on the pHcriterion given by Regulation (EC) No. 1272/2008 (CLP) It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification. The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products. A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle

### 16.6 Additional information available from:

Protectcoat International

Postbus 36

5430 AA CUIJK

+31(0)85 0655797

[www.protectcoatint.com](http://www.protectcoatint.com)

Last update: 01/01/2022