

Protectcoat AGR4

Description

Protectcoat AGR4 is a graffiti remover in gel form. The graffiti remover is suitable for removing graffiti from surfaces such as bricks, granite, concrete, marble, slate, sandstone, limestone, tiles etc. The **Protectcoat AGR4** is biodegradable.

Usage

Protectcoat AGR4 can be applied on:

- Bricks
- Concrete
- Marble
- Slate
- Limestone
- Etcetera.

Advantage

The advantages of **Protectcoat AGR4** are:

- Removes graffiti easily
- Economical in use
- Quick result
- Biodegradable

Application Tools

Apply **Protectcoat AGR4** with a brush, paintbrush or a roller:



Health and Safety

- Breathing Protection: No breathing protection is required under normal use conditions with suitable ventilation. Wearing a facemask is advisable.
- Hand protection: Chemical resistant gloves should be worn.
- Skin protection: Wear protective clothing over exposed areas of skin.
- Eye protection: Chemical goggles should be worn.
- Ingestion: Ingestion may cause nausea and vomiting. Do not induce vomiting. Consult a Doctor.

KEEP OUT OF THE REACH OF CHILDREN!

Recommendation

Always carry out a test first to ensure the finished result is acceptable.

Air temperature between 5°C – 30°C.
Substrate temperature 5°C – 25°C

Do not let the product dry in the sun.

Coverage rate

0,3 – 0,5m² / liter.

Depending on the degree of dirt.



Protectcoat AGR4

Application

Apply **Protectcoat AGR4** with a brush, paintbrush or a roller. Let the product dwell for 10-20 minutes. Depending on the degree of dirt. If necessary, use a brush or paintbrush to make sure the graffiti is dissolved.

Rinse the surface thoroughly with warm water under appropriate pressure. In case of multiple layer thicknesses or old graffiti residues, the application may have to be repeated.

To remove "shadows", the Protectcoat GRS4 can be used.

Equipment care

All equipment should be cleaned with water after use.

Storage

Recommended storage is in a cool, dry place with temperature 5°C – 30°C.

Shelf life: 12 months in original sealed container.

Technical Support

For technical support, please do not hesitate to contact us.

Protectcoat International

Spinding 16

5431 SN CUIJK

The Netherlands

Postbus 36

5430 AA CUIJK

The Netherlands

T: +31 (0)85-06 55 797

W: www.protectcoatint.com

Follow us on Social Media.



Important:

The content of this documentation is based on our experience with the product. Protectcoat International guarantees the quality of this products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Protectcoat International products or adverse weather conditions. For more information, consult the Safety Data Sheet. Protectcoat International accepts no liability arising from printing errors, mistakes/typing errors.

For the latest information, visit our website.

www.protectcoatint.com

Last updated: 01/01/2022